

| Li-Ion Cylindrical Battery Specification |                 |                  |                 |              |                    |                           |                 |        |        |
|------------------------------------------|-----------------|------------------|-----------------|--------------|--------------------|---------------------------|-----------------|--------|--------|
| Model No.                                | Nominal Voltage | Nominal Capacity | Standard Charge | Rapid Charge | Standard Discharge | Max. Continuous Discharge | Dimensions (mm) |        | Weight |
|                                          | V               | mAh              | mA              | mA           | mA                 | mA                        | Diameter        | Height | g      |
| ICR10440                                 | 3.6             | 300              | 60              | 300          | 60                 | 300                       | 10.5            | 44.0   | 10.0   |
| ICR14500                                 | 3.6             | 700              | 140             | 700          | 140                | 700                       | 14.5            | 50.5   | 20.0   |
| ICR14650                                 | 3.6             | 1050             | 210             | 1050         | 210                | 1050                      | 14.5            | 65.5   | 28.0   |
| ICR17335                                 | 3.6             | 650              | 130             | 650          | 130                | 650                       | 17.5            | 34.0   | 20.0   |
| ICR17500                                 | 3.6             | 1300             | 260             | 1300         | 260                | 1300                      | 17.5            | 50.0   | 33.0   |
| ICR17650                                 | 3.6             | 1600             | 320             | 1600         | 320                | 1600                      | 17.5            | 65.5   | 40.0   |
| ICR18500                                 | 3.6             | 1500             | 300             | 1500         | 300                | 1500                      | 18.5            | 65.5   | 33.0   |
| ICR18650                                 | 3.6             | 2000             | 400             | 2000         | 400                | 2000                      | 18.5            | 65.5   | 43.0   |
| ICR18650                                 | 3.6             | 2200             | 440             | 2200         | 440                | 2200                      | 18.5            | 65.5   | 45.0   |
| ICR18650                                 | 3.6             | 2400             | 480             | 2400         | 480                | 2400                      | 18.5            | 65.5   | 46.0   |
| ICR18650                                 | 3.6             | 2600             | 520             | 2600         | 520                | 2600                      | 18.5            | 65.5   | 46.0   |
| ICR22650                                 | 3.6             | 3200             | 640             | 3200         | 640                | 3200                      | 22.5            | 65.5   | 63.5   |
| ICR26650                                 | 3.6             | 5000             | 1000            | 5000         | 1000               | 5000                      | 26.5            | 65.5   | 93.0   |